



Sealants, Inc.

PRODUCT DATA

1088

CORK INSULATION TAPE

DESCRIPTION:

1088 Cork Insulation Tape was developed as an insulating material for the refrigeration and air conditioning industries to prevent condensation on cold pipes in air conditioning systems, freezers, commercial refrigeration or wherever problems of condensation are encountered. 1088 also provides an effective sound deadening barrier and can be used as a gasket material. It has excellent adhesion to all types of substrates and its ease of application make it adaptable for all cold insulating and sound deadening applications. 1088 is designed for easy application by hand and will not harden, skin over or lose flexibility. It is not toxic or irritating to the skin.

APPLICATION:

Apply by hand to clean, dry surfaces. 1088 may be applied directly to the surface as the roll is unwound or may be cut to length and applied. Wind the tape around the pipe, overlapping about ¼-inch to effect a continuous seal around the pipe. Apply hand pressure to ensure good adhesion to itself and to the substrate.

PROPERTIES:

Composition:	Select grades of ground virgin cork and synthetic elastomeric materials.
Color:	Black
K-Factor:	0.88 BTU-in/hr-ft ² -F°
Percent Solids (7-days @ 250°F):	100%
Weight per Gallon (ASTM D-71):	6.7 ± 0.5 pounds/gallon
Specific Gravity:	0.80 ± 0.10
Adhesion:	Excellent to clean metal, glass, plastic, rubber or painted surfaces. Needs no adhesives, bonds firmly to substrates and to itself.
Odor:	Imparts no odor. Can be used without danger of contamination
Shrinkage:	Will not shrink, dry out or pull away from surface.
Compatibility:	Will not effect rubber, plastic, oil based paint/stains and most latex paints.

Packaging:

Customer specific. Can be extruded flat or wound into rolls.

Shelf Life:

Non-hardening material that may be stored indefinitely.

For technical assistance, customer service and general information please call:

deVan Sealants, Inc.
6301 Prescott Avenue · P.O. Box 470375
St. Louis, MO 63147
(314) 383-1941 · Fax (314) 383-6491

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.

F:\Word\TDS\1088CorkTape.doc
2009/07/27