



Sealants, Inc.

PRODUCT DATA

402T

SOUND DEADENING and SEALING COMPOUND

PRODUCT DESCRIPTION:

402T is a sealing compound that is especially compounded for sound deadening applications. It can be used for noise and vibration damping applications in the appliance, transportation and construction industries. 402T is freeze-thaw stable and resistant to fungus of the following types: Chaetomium Globosum, Aspergillus Niger, Aspergillus Flavus and Penicillium Funiculosm.

402T has aggressive adhesion to most commercial surfaces without any special surface preparation.

PROPERTIES:

Color (ASTM D1729):	Gray
Odor (ASTM D1833):	None
Weight per Gallon (ASTM D71):	15.0 ± 0.5 pounds/gallon
Consistency (ASTM D217):	108 – 118 dmm
Light Discoloration (ASTM D1148):	1000-hours with no apparent change (S-1 sunlamp)
Freeze – Thaw Stability:	25,000 cycles of 1-min @ + 80°F + 3-min @ 0°F.
Adhesion:	100% cohesive failure on most commercial surfaces.
Service Temperature:	-40°F to 300°F
Flow:	No flow after 18-hours at 300°F on copper pipe.
Staining:	Non-staining
Toxicity:	Non-toxic. Do not take internally.

For technical assistance, customer service and general information, please contact us at:

deVan Sealants, Inc.
6301 Prescott Avenue · P.O. Box 470375
St. Louis, MO 63147
(314) 383-1941 · Fax (314) 383-6491

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.