



Sealants, Inc.

PRODUCT DATA

546.11

BURIAL VAULT SEALANT

DESCRIPTION:

546.11 Burial Vault Sealer is an elastomeric product with excellent adhesion to concrete, metal and plastics creating a seal against air, dust and moisture. It is resistant to water and will not harden, skin over or lose flexibility. 546.11 Burial Vault Sealer remains flexible at 0°F and functional at 200°F. 546.11 Burial Vault Sealer is non-toxic and requires no special handling equipment.

INSTALLATION PROCEDURE:

Joint surfaces should be clean and dry. The sealer may be applied directly to the substrate, as the roll is unwound. Apply hand pressure to ensure good adhesion to the substrate.

PROPERTIES:

Composition:	Butyl elastomer, tackifier and inert filler
Color:	Black
Percent Solids (7-days @ 250°F):	100%
Specific Gravity:	1.60 ± 0.10
Needle Penetration Hardness (ASTM D1321): @ 77°F	70 – 80 dmm
Tensile Yield Strength (ASTM C907):	30 psi typical
Service Temperature:	0°F to 200°F
Storage Stability:	Non-hardening material that may be stored indefinitely.

This data is based on tests believed to be reliable and is given for information purposes only.

deVan Sealants, Inc.
6301 Prescott Avenue · P.O. Box 470375
St. Louis, MO 63147
(314) 383.1941 · Fax (314) 383.6491

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.

F:\Word\TDS\546.11Vault.doc
2010-03-29