



PRODUCT DATA

545C.11

FOUNDATION TAPE

DESCRIPTION:

545C.11 is an elastic compound designed to act as a sealant between concrete foundations and metal grain bins, pre-engineered buildings, vaults or other structures. 545C.11 contains 0.125-inch spacers which keep it from squeezing out of the joint and allow it to function as a gasket and sealing material.

Adhesion of 545C.11 is excellent to dry, dust free, commercially clean surfaces such as rubber, asphalt, concrete, glass, plastic, wood, or painted surfaces. 545C.11 has good surface tack and adhesion will accumulate over time. It will form a bond to oil coated wood within 24 hours. It can be applied to surfaces at 35°F and can be molded by hand to fit any shape. 545C.11 bonds firmly to itself and needs no supplemental adhesive.

545C.11 is freeze-thaw stable. It is compatible with most paints but some oil-based paints will stain, test on a small area before applying.

PROPERTIES:

Property	Test Method	Typical Values
Color	ASTM D1729	Black
Odor		Mild to none
Service Temperature		-40°F to 180°F
Cone Penetration, 300 g	ASTM D217	80 – 90 dmm
% Solids	ASTM C771	>99% by weight
Specific Gravity	ASTM D297	0.98 ± 0.05 g/cm ³
Weight per Gallon		8.2 ± 0.5 pounds per gallon
Tensile Yield	ASTM C907	40 psi with cohesive failure
Elongation	ASTM C907	200% @ 0°F 1000% @ 77°F
Weatherability	ASTM D750	No apparent change of physical properties after 1000-hours QUV exposure.
Dielectric Strength		21,000 volts @ 1/8-inch thick
Chemical Resistance	96-hours immersion @ 120°F	No weight loss or change in consistency exposed to: <ul style="list-style-type: none"> - 58% and 85% phosphoric acid solution - 35% nitric acid solution - 35% hydrochloric acid solution - 35% sulfuric acid solution - 35% sodium hydroxide solution - 60% ammonium nitrate solution - 25% urea solution
Exposure Resistance		No deterioration exposed to: <ul style="list-style-type: none"> - 1,800-hours salt spray - 5-years underground exposure
Shelf Life		Minimum 1-year when stored in the original container at normal warehouse temperatures.

deVan Sealants, Inc.

6301 Prescott Avenue · P.O. Box 470375

St. Louis, MO 63147

(314) 383-1941 · Fax (314) 383-6491

www.devansealants.com

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.

2012-11-01