



## PRODUCT DATA

# 401.2

## EXTRUDED BEAD SEALER

### DESCRIPTION:

401.2 is a general purpose, thumb-grade sealer used for water, dust, air sealing and sound deadening applications. It is used in the assembly of automobiles, trailers, refrigerator cabinets, railroad cars, pre-fabricated buildings and other areas wherever a non-staining, non-hardening, non-drying sealer is required.

401.2 sealer is compatible with plastics, rubber and paint. It may be painted over without softening or discoloring paint. It will withstand normal bake cycles without hardening or cracking. 401.2 exhibits good adhesion to commercially clean surfaces. It is insoluble in water but soluble in hydrocarbon solvents. 401.2 is available in extruded bead or tape form.

### PHYSICAL PROPERTIES:

Property	Test Method	Typical Values
Color	ASTM D1729	Off-white
Odor		No objectionable odors.
Service Temperature		-20°F to 350°F
Needle Penetration, 100 g	ASTM D1321	100 – 110 dmm
% Solids	ASTM C771	100%
Specific Gravity	ASTM D297	1.78 ± 0.05 g/cm <sup>3</sup>
Weight per Gallon		14.8 ± 0.5 pounds per gallon
Shelf Life		Non-hardening material that may be stored indefinitely.

### deVan Sealants, Inc.

6301 Prescott Avenue · P.O. Box 470375

St. Louis, MO 63147

(314) 383-1941 · Fax (314) 383-6491

[www.devansealants.com](http://www.devansealants.com)

#### CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.

2012-11-12