



PRODUCT DATA

404

THUMBING COMPOUND

DESCRIPTION:

404 Thumbing Compound is a general-purpose product used to seal against water, dust and air. It can also be used as a noise and sound deadener. 404 is used in the assembly or repair of automobiles, trailers, refrigerator cabinets, HVAC, railroad cars, pre-fabricated buildings and numerous other uses. It can be used wherever a non-staining, non-hardening, non-drying sealer is required.

404 Thumbing Compound has good adhesion to commercially clean surfaces and does not affect plastic, rubber or paint. It can be painted without softening or discoloring paint and will withstand normal baking cycles. It is insoluble in water but soluble in hydrocarbon solvents.

404 is available in extruded bead, tape or slug form.

PROPERTIES:

Property	Test Method	Typical Values
Color	ASTM D1729	404.2: Off white 404.7: Beige
Odor		No objectionable odors.
Service Temperature		-10°F to 350°F
Needle Penetration, 100-g	ASTM D1321	110 – 150 dmm
% Solids	ASTM C771	100%
Specific Gravity	ASTM D297	1.81 ± 0.05 g/cm ³
Weight per Gallon		15.1 ± 0.5 pounds per gallon
Sag	TP-007	Passes 30-minutes @ 350°F
Flexibility	ASTM C765	Passes 1-inch mandrel bend @ -10°F
Discoloration from Ultraviolet Light Exposure	ASTM D1148, 1000-hrs QUV exposure	No apparent change.
Shelf Life		Non-hardening material that may be stored indefinitely.

deVan Sealants, Inc.

6301 Prescott Avenue · P.O. Box 470375

St. Louis, MO 63147

(314) 383-1941 · Fax (314) 383-6491

www.devansealants.com

CONDITIONS OF SALE AND LIMITATIONS OF WARRANTIES:

All deVan Sealants, Inc. products and materials are sold subject to the terms and conditions set forth in the technical data sheet, invoice, order acknowledgement and/or bill of lading. All statements, technical information and recommendations regarding such products are based on tests and examinations believed to be reliable but deVan Sealants, Inc. neither guarantees nor warrants their accuracy or completeness.

It shall be the sole responsibility of the user to determine the suitability of the deVan Sealants, Inc. product or material for each intended use and the user shall assume all risks and liability in connection with the use, or inability to use, the product or material.

To the exclusion of all other remedies, deVan Sealants, Inc. warrants and agrees to replace or, as its sole option, to refund the purchase price of that portion of any material or product supplied by deVan Sealants, Inc. which is proven, upon inspection within thirty (30) days of the date of receipt of such product or material, to be defective in material or workmanship. No salesperson, agent, employee or representative of deVan Sealants, Inc. has any authority to enlarge or change the terms of the warranty.

In no event shall deVan Sealants, Inc. be responsible for any special, indirect, consequential or incidental damages or loss including, without limitations, loss of profits or revenues, economic losses or loss of use, whether statutory or based on theories of contract or tort. THERE ARE NO OTHER AGREEMENTS, UNDERSTANDINGS, REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED (INCLUDING ANY REGARDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE) NOT SPECIFIED HEREIN.

2012-11-14